

MODEL	3.0 AT6	3.0 AT6
DRIVE CONFIGURATION	4X2	4X4
INTERIOR FEATURES		
Power-Assisted Steering (PAS)	Standard	Standard
Steering Column Adjustment	Manual / Tilt	Manual / Tilt
Leather Steering Wheel with Multi-Function Controls	Standard	Standard
Gearknob Trim	Urethane with Decorative Plate	Urethane with Decorative Plate
Seating Capacity	7	7
Front Seat Configuration	2 x Reclining Bucket Seats	2 x Reclining Bucket Seats
Second-Row Seat Configuration	60:40 Fold-Flat Bench	60:40 Fold-Flat Bench
Third-Row Seat Configuration	50:50 Fold-Flat Bench	50:50 Fold-Flat Bench
Seat Trim	Leather	Leather
Seat Adjustment	Driver Power (6-Way)	Driver Power (6-Way)
Seatbelt Reminder	Driver & Passenger	Driver & Passenger
Rear Seat Centre Armrest	Standard with 2 Cupholders	Standard with 2 Cupholders
Storage Pockets behind Front Seats	Standard	Standard
Floor Trim	Carpet with Heel Pad	Carpet with Heel Pad
Driver Footrest	Standard	Standard
Air-Conditioner	Automatic Climate Control	Automatic Climate Control
Inside Rear-View Mirror	Standard	Standard
Sunvisor	Driver & Passenger with Vanity Mirror & Driver Ticketholder	Driver & Passenger with Vanity Mirror & Driver Ticketholder
Overhead Console with Sunglasses Holder	Standard	Standard
Digital Clock	Standard	Standard
Cruise Control	Standard	Standard
Multi-Information Display (MID)	Standard	Standard
Dashboard Illumination Control	Standard	Standard
Power Windows	All with Driver Auto Up / Down, with Jam Protection, with Timer	All with Driver Auto Up / Down, with Jam Protection, with Timer
Auxiliary 12-V Power Socket	2	2
Lockable Glove Box	Standard with Illumination	Standard with Illumination
Door Trim with Storage Pockets & Integrated Cupholders	Standard	Standard
Floor Tunnel / Console with Integrated Cupholder	Standard	Standard
Centre Console Storage Box with Lid	Standard	Standard
Storage Box	Standard	Standard
Rear Privacy Windows	Standard	Standard
Fixed Rear Window with Defogger	Standard	Standard
INFOTAINMENT		
Audio System	6.5" Touchscreen with RDS, Frontloading DVD Player, MP3, Bluetooth® Audio Streaming with Integrated Mobile Hands-free, Satellite Navigation, Rear-View Camera	6.5" Touchscreen with RDS, Frontloading DVD Player, MP3, Bluetooth® Audio Streaming with Integrated Mobile Hands-free, Satellite Navigation, Rear-View Camera
Audio Input Terminal: USB, Auxiliary	Standard	Standard
No. of Speakers	8	8
Steering Wheel Audio Controls	Standard	Standard
OPTIONS		
Audio System	9" Touchscreen with RDS, Bluetooth® Audio Streaming, Bluetooth® Phone, 2DIN Flush, Satellite Navigation, Rear-View Camera	9" Touchscreen with RDS, Bluetooth® Audio Streaming, Bluetooth® Phone, 2DIN Flush, Satellite Navigation, Rear-View Camera
Metallic Paint	Available	Available
WARRANTY / SERVICE INTERVALS		
Warranty & Roadside Assistance	5 Years / 120 000 km	5 Years / 120 000 km
Anti-Corrosion Warranty	5 Years / Unlimited km	5 Years / Unlimited km
Service Plan	5 Years / 90 000 km	5 Years / 90 000 km
Service Intervals	12 Months / 15 000 km	12 Months / 15 000 km

(#1) Fuel Economy & CO₂ data as per ECE R101 / SANS 20101 Regulation. Note that the actual fuel consumption will depend on many factors, including the driver's driving habits, prevailing conditions & the vehicle's equipment, condition & use.
 (#2) Towing capacity subject to South African Road Traffic Act. The weight of the towing vehicle including trailer towball load must not exceed the Gross Vehicle Mass (GVM). The combined weight of the fully loaded vehicle & trailer must not exceed the Gross Combination Mass (GCM). Maximum individual axle loads (GA1 & GA2) must not be exceeded. (e.g.: if a 3.0 L Diesel is towing 3.500 kg its Maximum Vehicle Mass is 2.500 kg in order to be within GCM).
 (#3) Payload – preliminary data shown for mu-X models. Date of print May 2018.

ISUZU MU-X

Specification Sheet



www.isuzu.co.za f t

ISUZU
 With you, for the long run

MODEL	3.0 AT6	3.0 AT6
DRIVE CONFIGURATION	4X2	4X4
ENGINE		
Engine	4JJ1TC HI	4JJ1TC HI
Displacement (cc)	2999	2999
No. of Cylinders	4	4
Compression Ratio	17.3:1	17.3:1
Bore X Stroke (mm)	95.4 X 104.9	95.4 X 104.9
No. of Valves	16	16
Power (kW) @ r/min	130 @ 3600	130 @ 3600
Torque (Nm) @ r/min	380 @ 1800 – 2800	380 @ 1800 – 2800
Turbocharger	Standard	Standard
FUEL CONSUMPTION (#1)		
Combined Cycle (l/100 km)	7.3	7.9
Combined CO ₂ Emissions (g/km)	194	208
Fuel Type	Diesel	Diesel
TRANSMISSION		
Transmission Type	6-Speed Automatic	6-Speed Automatic
Gear Ratio: 1st	3.600	3.600
Gear Ratio: 2nd	2.092	2.092
Gear Ratio: 3rd	1.488	1.488
Gear Ratio: 4th	1.000	1.000
Gear Ratio: 5th	0.687	0.687
Gear Ratio: 6th	0.580	0.580
Gear Ratio: Reverse	3.732	3.732
4WD Selector	-	Standard
Low Range Ratio	-	2.482
REAR DIFFERENTIAL		
Axle Ratio: Final Drive	3.727	3.727
CHASSIS DESIGN		
Front Wheel Suspension	Independent High-Ride Coil	Independent High-Ride Coil
Rear Wheel Suspension	Multi-Link Coil	Multi-Link Coil
Shock Absorbers	Gas	Gas
High-Ride Suspension	Standard	Standard
Skid Plate Guard	Standard	Standard
Engine Sump Guard	-	Standard
Transfer Case Guard	-	Standard
WHEELS & TYRES		
Tyre Size	255 / 60 R18	255 / 60 R18
Wheel Size / Type	18" X 7.0J Alloy	18" X 7.0J Alloy
Spare Wheel Size / Type	18" X 7.0J Alloy	18" X 7.0J Alloy
Turning Circle (m)	11.6	11.6
DIMENSIONS		
Length (mm)	4825	4825
Width (mm)	1860	1860
Height (mm)	1860	1860
Wheelbase (mm)	2845	2845
Front / Rear Track (mm)	1570 / 1570	1570 / 1570
Ground Clearance (mm)	230	230
Approach Angle (°)	24.0	24.0
Departure Angle (°)	25.1	25.1
Breakover Angle (°)	19.5	22.4
Wading Depth (mm)	600	600

MODEL	3.0 AT6	3.0 AT6
DRIVE CONFIGURATION	4X2	4X4
MASS / CAPACITIES		
Gross Vehicle Mass – (GVM) (kg)	2650	2750
Gross Combined Mass – (GCM) (kg)	5650	5750
Tare Mass (kg)	1990	2085
Payload (kg) (#3)	612	617
Towing Capacity (kg): Unbraked Trailer (#2)	750	750
Towing Capacity / Rating (kg): Braked Trailer (#2)	3000	3000
Fuel Tank Capacity (Litres)	65	65
SAFETY FEATURES		
Anti-Lock Braking System (ABS)	Standard	Standard
Electronic Brake-Force Distribution (EBD)	Standard	Standard
Brake-Assist System (BAS)	Standard	Standard
Electronic Stability Control (ESC) with Traction Control	Standard	Standard
Hill-Start Assist (HAS)	Standard	Standard
Hill Descent Control (HDC)	Standard	Standard
Trailer Sway Control	Standard	Standard
Height-Adjustable 3-Point Seatbelts	Standard	Standard
Seatbelt Pre-Tensioners	Standard	Standard
Driver & Front Passenger Airbags	Standard	Standard
Front Seat Side Airbags	Standard	Standard
Curtain Airbags	Standard	Standard
Collapsible Steering Column	Standard	Standard
Speed-Sensitive Door Lock	Standard	Standard
ISOFIX Child Seat Attachment	Standard	Standard
Rear-View Camera	Standard	Standard
SECURITY FEATURES		
Remote-Controlled Central Locking	Standard	Standard
Passive Entry Start System (PESS)	Standard	Standard
Anti-Theft Alarm System	Standard	Standard
Transponder Immobiliser System	Standard	Standard
INTERIOR / EXTERIOR LIGHTING		
Front Reading Lamps	Standard	Standard
Interior Courtesy Lamps	Standard	Standard
Luggage Lamp	Standard	Standard
Front Fog Lights	Standard	Standard
Daytime Running Lights (DRL)	LED	LED
Headlights	Bi-LED	Bi-LED
Headlights 'ON' Warning Buzzer	Standard	Standard
Headlamp Levelling	Automatic	Automatic
LED Combination Rear Taillights	Standard	Standard
Centre High-Mounted Stoplight	LED	LED
EXTERIOR FEATURES		
Radiator Grille – Colour	Chrome	Chrome
Front Bumper – Colour	Body Colour Upper / Medium Grey Lower	Body Colour Upper / Medium Grey Lower
Rear Bumper – Colour	Body Colour Upper / Medium Grey Lower	Body Colour Upper / Medium Grey Lower
Exterior Door Handles – Colour	Chrome	Chrome
Exterior Mirrors	Chrome, Power Adjustable, Retractable, Heated with Side Indicator	Chrome, Power Adjustable, Retractable, Heated with Side Indicator
Side-Steps	Standard	Standard
Mudflaps	Front & Rear	Front & Rear
Roof Rails	Standard	Standard
Rear Window Wiper	Standard	Standard

(#1) Fuel Economy & CO₂ data as per ECE R101 / SANS 20101 Regulation. Note that the actual fuel consumption will depend on many factors, including the driver's driving habits, prevailing conditions & the vehicle's equipment, condition & use.

(#2) Towing capacity subject to South African Road Traffic Act. The weight of the towing vehicle including trailer towball load must not exceed the Gross Vehicle Mass (GVM). The combined weight of the fully loaded vehicle & trailer must not exceed the Gross Combination Mass (GCM). Maximum individual axle loads (GA1 & GA2) must not be exceeded. (e.g.: if a 3.0 L Diesel is towing 3.500 kg its Maximum Vehicle Mass is 2.500 kg in order to be within GCM). Date of print May 2018.

(#3) Payload – preliminary data shown for mu-X models